

# Win - 100CK

Dome keyboard



### Features :

Keyboard to Control

- KB High Speed Dome (all models)

Connection

- RS485, RS422 & USB

Functions

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern
- Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips



## Technical Specification

### General

Keyboard Key panel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RS485, RS422
Keyboard Communication	Direct Mode
Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P, etc
Network Mode	N/A
Display	LCD, 75.2mm×33.85mm

### Environmental

Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/1000mA
Power Consumption	5W
Working Temperature	-10C~+55C
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mm×160(140)mm×37.5(21)mm (W×D×H)(height: 100mm including joystick)
Weight	2.5kg (Including package)